

► Specification

Product code	13441035
Product construction	Tufted High & Low Loop
Face yarn	Solution dyed Nylon [Econyl®] [Regenerated Solution Dyed Nylon]
Gauge	1/12 inch
Stitches	42/10cm
Pile height	6.0/2.5mm (±0.5mm)
Pile weight	540g/m <sup>2</sup>
Total thickness	7.5mm (±0.5mm)
Backing	Post consumer recycled PVC'ECOS®'
Size	50×50cm
Weight	4.7kg/m <sup>2</sup>
Flame retardancy	E2230044
Antistatic property	Less than 1,000V (JIS L-4406,23°C, 25% RH, synthetic sole)
Packing	16pieces(4m <sup>2</sup> )/case



Post-consumer  
Regenerated PVC Backing




Total regenerated  
material content




Reduction of CO<sub>2</sub>  
emission


► Installation Method




monolithic



quarter turn



ashlar



blic



Green Label  
Plus



Eco Mark by Japan  
Environment  
Association(Inc)



原着糸使用  
Solution Dyed Nylon



F☆☆☆☆☆  
Low VOC



**SUMINOE Interior Products Co., Ltd.**

Shinmachi 2-4-2, Nishi-ku Osaka 550-0013, Japan

Tel: +81(6)6537-6325 Fax: +81(6)6537-6311 Mail: global@sin.suminoe.co.jp

<http://carpet-tiles.jp/>